

GE Betz

GE Betz, Inc.

Material Safety Data Sheet

4636 Somerton Road

Issue Date: 04-APR-2002

Trevose, PA 19053

Business telephone: (215) 355-3300

EMERGENCY TELEPHONE (Health/Accident): (800) 877-1940

1 PRODUCT IDENTIFICATION

REAGENT NAME:

METHYL PURPLE INDICATOR

REAGENT CODE:

L297

REAGENT APPLICATION AREA:

FIELD TEST REAGENT

2 COMPOSITION / INFORMATION ON INGREDIENTS

Information for specific product ingredients as required by the U.S. OSHA HAZARD COMMUNICATION STANDARD is listed. Refer to additional sections of this MSDS for our assessment of the potential hazards of this formulation.

HAZARDOUS INGREDIENTS:

CAS#

CHEMICAL NAME

67-63-0

ISOPROPYL ALCOHOL (IPA)

Flammable liquid; chronic overexposure may cause

liver and kidney toxicity

No component is considered to be a carcinogen by the National Toxicology Program, the International Agency for Research on Cancer, or the Occupational Safety and Health Administration at OSHA thresholds for carcinogens.

3 HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING

May cause slight irritation to the skin. May cause moderate irritation to the eyes. Vapors, gases, mists and/or aerosols may cause irritation to upper respiratory tract.

DOT hazard: Flammable liquid Emergency Response Guide #27

Odor: Alcohol; Appearance: Dark Green, Liquid

Fire fighters should wear positive pressure self-contained breathing apparatus(full face-piece type). Proper fire-extinguishing media:
dry chemical, carbon dioxide or foam--Avoid water if possible.

POTENTIAL HEALTH EFFECTS

ACUTE SKIN EFFECTS:

Primary route of exposure; May cause slight irritation to the skin.

ACUTE EYE EFFECTS:

May cause moderate irritation to the eyes.

ACUTE RESPIRATORY EFFECTS:

Primary route of exposure; Vapors, gases, mists and/or aerosols may cause irritation to upper respiratory tract.

INGESTION EFFECTS:

May cause gastrointestinal irritation with possible nausea, vomiting, diarrhea, incoordination, mental confusion, dizziness and lethargy.

TARGET ORGANS:

Prolonged or repeated exposures may cause defatting-type dermatitis and/or toxicity to the liver and kidney.

MEDICAL CONDITIONS AGGRAVATED:

Not known.

SYMPTOMS OF EXPOSURE:

Excessive dermal exposure causes defatting and drying of skin. Excessive inhalation of vapors causes dizziness, headache and nausea.

4 FIRST AID MEASURES

SKIN CONTACT:

Wash thoroughly with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

EYE CONTACT:

Remove contact lenses. Hold eyelids apart. Immediately flush eyes with plenty of low-pressure water for at least 15 minutes. Get immediate medical attention.

INHALATION:

Remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. Get immediate medical attention.

INGESTION:

Do not feed anything by mouth to an unconscious or convulsive victim. Do not induce vomiting. Immediately contact physician. Dilute contents of stomach using 3-4 glasses milk or water.

NOTES TO PHYSICIANS:

No special instructions

5 FIRE FIGHTING MEASURES

FIRE FIGHTING INSTRUCTIONS:

Fire fighters should wear positive pressure self-contained breathing apparatus (full face-piece type).

EXTINGUISHING MEDIA:

dry chemical, carbon dioxide or foam -- Avoid water if possible.

HAZARDOUS DECOMPOSITION PRODUCTS:

Thermal decomposition (destructive fires) yields elemental oxides.

FLASH POINT:

 $\mathfrak{D}_{\mathcal{F}}$

90F 32C P-M(CC)

MISCELLANEOUS:

Flammable liquid

UN1993; Emergency Response Guide #27

6 ACCIDENTAL RELEASE MEASURES

PROTECTION AND SPILL CONTAINMENT:

Ventilate area. Use specified protective equipment. Contain and absorb on absorbent material. Place in waste disposal container. Remove ignition sources. Flush area with water. Spread sand/grit.

DISPOSAL INSTRUCTIONS:

Water contaminated with this product may be sent to a sanitary sewer treatment facility, in accordance with any local agreement, a permitted waste treatment facility or discharged under a permit. Product as is - Incinerate or land dispose in an approved landfill.

7 HANDLING & STORAGE

HANDLING:

Flammable. Store in explosive proof area where electrical equipment meets NFPA code.

STORAGE:

Keep containers closed when not in use. Keep away from flames or sparks. Bond containers during filling or discharge when performed at temperatures at or above the product flash point.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS

CHEMICAL NAME

ISOPROPYL ALCOHOL (IPA)

PEL (OSHA): 400 PPM(500PPM-STEL)
TLV (ACGIH): 400 PPM(500PPM-STEL)

ENGINEERING CONTROLS:

Adequate ventilation to maintain air contaminants below exposure

PERSONAL PROTECTIVE EQUIPMENT:

Use protective equipment in accordance with 29CFR 1910 Subpart I RESPIRATORY PROTECTION:

A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA'S 29 CFR 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE.
USE AIR PURIFYING RESPIRATORS WITHIN USE LIMITATIONS ASSOCIATED

WITH THE EQUIPMENT OR ELSE USE SUPPLIED AIR-RESPIRATORS.

If air-purifying respirator use is appropriate, use a
respirator vapor cartridges.

SKIN PROTECTION:

neoprene gloves-- Wash off after each use. Replace as necessary.

EYE PROTECTION:

splash proof chemical goggles

9 PHYSICAL & CHEMICAL PROPERTIES

Specific Grav.(70F,21C) 1.000 Vapor Pressure (mmHG) 14.0
Freeze Point (F) ND Vapor Density (air=1) < 1.00
Freeze Point (C) ND
Viscosity(cps 70F,21C) ND % Solubility (water) ND

Odor
Appearance
Appearance
Physical State
Flash Point
P-M(CC)
PH As Is (approx.)
Evaporation Rate (Ether=1)

Alcohol
Dark Green
Liquid
90F 32C
7.1

NA = not applicable ND = not determined

10 STABILITY & REACTIVITY

STABILITY:

Stable under normal storage conditions.

HAZARDOUS POLYMERIZATION:

Will not occur.

INCOMPATIBILITIES:

May react with strong oxidizers.

DECOMPOSITION PRODUCTS:

Thermal decomposition (destructive fires) yields elemental oxides.

INTERNAL PUMPOUT/CLEANOUT CATEGORIES:

"B"

11 TOXICOLOGICAL INFORMATION

Oral LD50 RAT: >2,000 mg/kg

NOTE - Estimated value

>2,000 mg/kg

Dermal LD50 RABBIT:

NOTE - Estimated value

12 ECOLOGICAL INFORMATION

AQUATIC TOXICOLOGY

No Data Available.

BIODEGRADATION

No Data Available.

13 DISPOSAL CONSIDERATIONS

If this undiluted product is discarded as a waste, the US RCRA hazardous waste identification number is: D001=Ignitable.

Please be advised; however, that state and local requirements for waste disposal may be more restrictive or otherwise different from federal regulations. Consult state and local regulations regarding the proper disposal of this material.

14 TRANSPORT INFORMATION

DOT HAZARD: Flammable liquid

UN / NA NUMBER: UN1993

DOT EMERGENCY RESPONSE GUIDE #: 27

15 REGULATORY INFORMATION

TSCA:

All components of this product are listed in the TSCA inventory.

CERCLA AND/OR SARA REPORTABLE QUANTITY (RQ):

No regulated constituent present at OSHA thresholds

SARA SECTION 312 HAZARD CLASS:

Immediate (acute); Delayed (Chronic); Fire

SARA SECTION 302 CHEMICALS:

No regulated constituent present at OSHA thresholds

SARA SECTION 313 CHEMICALS:

No regulated constituent present at OSHA thresholds

CALIFORNIA REGULATORY INFORMATION

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65) CHEMICALS PRESENT:

No regulated constituent present at OSHA thresholds MICHIGAN REGULATORY INFORMATION

No regulated constituent present at OSHA thresholds

16 OTHER INFORMATION

NFPA/HMIS

CODE TRANSLATION

Health	1	Slight Hazard
Fire	3	Serious Hazard
Reactivity	0	Minimal Hazard
Special	NONE	No special Hazard
(1) Protective Equipment	В	Goggles, Gloves

(1) refer to section 8 of MSDS for additional protective equipment recommendations.

CHANGE LOG

EFFECTIVE	E.	F.	FΕ	C	Т	I.	V	Ε
-----------	----	----	----	---	---	----	---	---

	DATE	REVISIONS TO SECTION:	SUPERCEDES
MSDS status:	22-AUG-1995	REVISED FORMAT	** NEW **
	04-APR-2002	4	22-AUG-1995